

# Cisco Firepower 1000 Series

Cisco Secure Firewall ASA

Cisco Secure Firewall Threat Defense (FTD)

---

# Contents

Cisco Firepower 1000 Series Appliances .....	3
Model overview .....	3
Cisco Firepower 1000 Series summary .....	3
Detailed performance specifications and feature highlights .....	4
Hardware specifications .....	7
Cisco Capital .....	9
Flexible payment solutions to help you achieve your objectives .....	9

## Cisco Firepower 1000 Series Appliances

The Cisco Firepower® 1000 Series is a family of four firewall platforms that deliver business resiliency, management ease-of-use, and threat defense. They offer exceptional sustained performance when advanced threat functions are enabled. 1000 Series addresses use cases from small offices to remote branches. 1000 Series platforms run Cisco Threat Defense (FTD) and Cisco ASA software.

### Model overview



### Cisco Firepower 1000 Series summary

Model	Throughput: Threat Defense Software	IPS Throughput	Interfaces
FPR-1010	650 Mbps	650 Mbps	8 x RJ45
FPR-1120	1.5 Gbps	1.5 Gbps	8 x RJ45, 4 x SFP
FPR-1140	2.2 Gbps	2.2 Gbps	8 x RJ45, 4 x SFP
FPR-1150	3 Gbps	3 Gbps	8 x RJ45, 2 x SFP, 2 x 10G SFP+

## Detailed performance specifications and feature highlights

**Table 1.** Performance specifications and feature highlights for Cisco Firepower 1000 with the Threat Defense (FTD) image

Features	1010	1120	1140	1150
Throughput: Firewall (FW) + Application Visibility and Control (AVC) (1024B)	650 Mbps	1.5 Gbps	2.2 Gbps	3 Gbps
Throughput: FW + AVC + Intrusion Prevention System (IPS) (1024B)	650 Mbps	1.5 Gbps	2.2 Gbps	3 Gbps
Maximum concurrent sessions, with AVC	100K	200K	400K	600K
Maximum new connections per second, with AVC	6K	15K	22K	28K
Transport Layer Security (TLS)	150 Mbps	700 Mbps	1 Gbps	1.4 Gbps
Throughput: IPS (1024B)	650 Mbps	1.5 Gbps	2.2 Gbps	3 Gbps
IPSec VPN throughput (1024B TCP w/Fastpath)	300 Mbps	1 Gbps	1.2 Gbps	1.4 Gbps
Maximum VPN Peers	75	150	400	800
Cisco Device Manager (local management)	Yes	Yes	Yes	Yes
<b>Centralized management</b>	Centralized configuration, logging, monitoring, and reporting are performed by the Threat Defense Manager (FMC) or, alternatively, from the cloud with Cisco Defense Orchestrator			
<b>AVC</b>	Standard, supporting more than 4000 applications, as well as geolocations, users, and websites			
<b>AVC: OpenAppID support for custom, open-source application detectors</b>	Standard			
<b>Cisco Security Intelligence</b>	Standard, with IP, URL, and DNS threat intelligence			
<b>Cisco IPS</b>	Available; can passively detect endpoints and infrastructure for threat correlation and Indicators of Compromise (IoC) intelligence			
<b>Cisco Malware Defense for Networks</b>	Available; enables detection, blocking, tracking, analysis, and containment of targeted and persistent malware, addressing the attack continuum both during and after attacks. Integrated threat correlation with Cisco AMP for Endpoints is also optionally available			
<b>Cisco Malware Analytics sandboxing</b>	Available			
<b>URL filtering: number of categories</b>	More than 80			
<b>URL filtering: number of URLs categorized</b>	More than 280 million			

<b>Automated threat feed and IPS signature updates</b>	Yes: class-leading Collective Security Intelligence (CSI) from the Cisco Talos® group ( <a href="https://www.cisco.com/c/en/us/products/security/talos.html">https://www.cisco.com/c/en/us/products/security/talos.html</a> )
<b>Third-party and open-source ecosystem</b>	Open API for integrations with third-party products; Snort® and OpenAppID community resources for new and specific threats
<b>High availability and clustering</b>	Active/standby
<b>Cisco Trust Anchor Technologies</b>	Cisco Firepower 1000 Series platforms include Trust Anchor Technologies for supply chain and software image assurance. Please see the section below for additional details

Note: Performance will vary depending on features activated, and network traffic protocol mix, and packet size characteristics. Performance is subject to change with new software releases. Consult your Cisco representative for detailed sizing guidance.

**Table 2.** ASA Performance and capabilities on Firepower 1000 appliances

Features	1010	1120	1140	1150
Stateful inspection firewall throughput <sup>1</sup>	2 Gbps	4.5 Gbps	6 Gbps	7.5 Gbps
Stateful inspection firewall throughput (multiprotocol) <sup>2</sup>	1.4 Gbps	2.5 Gbps	3.5 Gbps	4.5 Gbps
Concurrent firewall connections	100,000	200,000	400,000	600,000
Firewall latency (UDP 64B microseconds)	-	-	-	-
New connections per second	25,000	75,000	100,000	150,000
IPsec VPN throughput (450B UDP L2L test)	500 Mbps	1 Gbps	1.2 Gbps	1.7 Gbps
Maximum VPN Peers	75	150	400	800
Security contexts (included; maximum)	NA	2; 5	2; 5	2; 25
High availability	Active/standby	Active/active and Active/standby	Active/active and Active/standby	Active/active and Active/standby
Clustering		-		
Scalability		VPN Load Balancing		
Centralized management		Centralized configuration, logging, monitoring, and reporting are performed by Cisco Security Manager or alternatively in the cloud with Cisco Defense Orchestrator		
Adaptive Security Device Manager		Web-based, local management for small-scale deployments		

## Performance testing methodologies [LINK](#)

1. Throughput measured with 1500B User Datagram Protocol (UDP) traffic measured under ideal test conditions.
2. "Multiprotocol" refers to a traffic profile consisting primarily of TCP-based protocols and applications like HTTP, SMTP, FTP, IMAPv4, BitTorrent, and DNS.

## Hardware specifications

**Table 3.** Cisco Firepower 1000 Series hardware specifications

Features	1010	1120	1140	1150
<b>Dimensions (H x W x D)</b>	1.82 x 7.85 x 8.07 in.	1.72 x 17.2 x 10.58 in.	1.72 x 17.2 x 10.58 in.	1.72 x 17.2 x 10.58 in.
<b>Form factor (rack units)</b>	DT	1RU	1RU	1RU
<b>Integrated I/O</b>	8 x RJ-45 (Includes 2 POE+ capable ports)	8 x RJ-45, 4 x SFP	8 x RJ-45, 4 x SFP	8 x RJ-45, 2 x 1Gbps SFP, 2 x 1/10Gbps SFP+
<b>Integrated network management ports</b>	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)
<b>Serial port</b>	1 x RJ-45 console	1 x RJ-45 console	1 x RJ-45 console	1 x RJ-45 console
<b>USB</b>	1 x USB 3.0 Type-A (500mA)	1 x USB 3.0 Type-A (500mA)	1 x USB 3.0 Type-A (500mA)	1 x USB 3.0 Type-A (500mA)
<b>Storage</b>	1 x 200 GB	1 x 200 GB	1 x 200 GB	1 x 200 GB
<b>Power supply configuration</b>	+12V and -53.5V	+12V	+12V	+12V
<b>AC input voltage</b>	100 to 240V AC	100 to 240V AC	100 to 240V AC	100 to 240V AC
<b>AC maximum input current</b>	< 2A at 100V, < 1A at 240V	< 2A at 100V, < 1A at 240V	< 2A at 100V, < 1A at 240V	< 2A at 100V, < 1A at 240V
<b>AC maximum output power</b>	115W (55W of +12V and 60W of -53.5V)	100W	100W	100W
<b>AC frequency</b>	50 to 60 Hz	50 to 60 Hz	50 to 60 Hz	50 to 60 Hz
<b>AC efficiency</b>	>88% at 50% load	>85% at 50% load	>85% at 50% load	>85% at 50% load
<b>Redundancy</b>	None	None	None	None
<b>Fans</b>	None	1 integrated fan <sup>2</sup>	1 integrated fan <sup>2</sup>	1 integrated fan <sup>2</sup>
<b>Noise</b>	0 dBA	31.7 dBA @ 25C, 56.8 dBA at highest system performance	34.2 dBA @ 25C, 56.8 dBA at highest system performance	34.2 dBA @ 25C, 56.8 dBA at highest system performance

Features	1010	1120	1140	1150
<b>Rack mountable</b>	Yes. Separate kit must be ordered.	Yes. Fixed mount brackets included (2-post).	Yes. Fixed mount brackets included (2-post).	Yes. Fixed mount brackets included (2-post).
<b>Weight</b>	3 lb (1.36 kg)	8 lb (3.63 kg)	8 lb (3.63 kg)	8 lb (3.63 kg)
<b>Temperature: operating</b>	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)
<b>Temperature: nonoperating</b>	-13 to 158°F (-25 to 70°C)	-13 to 158°F (-25 to 70°C)	-13 to 158°F (-25 to 70°C)	-13 to 158°F (-25 to 70°C)
<b>Humidity: operating</b>	90% noncondensing	90% noncondensing	90% noncondensing	90% noncondensing
<b>Humidity: nonoperating</b>	10 to 90% noncondensing	10 to 90% noncondensing	10 to 90% noncondensing	10 to 90% noncondensing
<b>Altitude: operating</b>	9843 ft (max) 3000 m (max)	9843 ft (max) 3000 m (max)	9843 ft (max) 3000 m (max)	9843 ft (max) 3000 m (max)
<b>Altitude: nonoperating</b>	15,000 ft (max)	15,000 ft (max)	15,000 ft (max)	15,000 ft (max)

Table 4. Cisco Firepower 1000 Series regulatory, safety, and EMC compliance

Specification	Description
<b>Regulatory compliance</b>	Products comply with CE markings per directives 2004/108/EC and 2006/108/EC
<b>Safety</b>	<ul style="list-style-type: none"> <li>• UL 60950-1</li> <li>• CAN/CSA-C22.2 No. 60950-1</li> <li>• EN 60950-1</li> <li>• IEC 60950-1</li> <li>• AS/NZS 60950-1</li> <li>• GB4943</li> </ul>
<b>EMC: emissions</b>	<ul style="list-style-type: none"> <li>• 47CFR Part 15 (CFR 47) Class A (FCC Class A)</li> <li>• AS/NZS CISPR22 Class A</li> <li>• CISPR22 CLASS A</li> <li>• EN55022 Class A</li> <li>• ICES003 Class A</li> <li>• VCCI Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• KN22 Class A</li> <li>• CNS13438 Class A</li> <li>• EN300386</li> <li>• TCVN7189</li> </ul>



Specification	Description
EMC: immunity	<ul style="list-style-type: none"> <li>• EN55024</li> <li>• CISPR24</li> <li>• EN300386</li> <li>• KN24</li> <li>• TVCN 7317</li> <li>• EN-61000-4-2, EN-61000-4-3, EN-61000-4-4, EN-61000-4-5, EN-61000-4-6, EN-61000-4-8, EN61000-4-11</li> </ul>

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you

acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)