



### Feature

- Third-party IP cameras supported with ONVIF conformance
- Dual gigabit network interfaces
- 8 HDDs, up to 32 TB
- Compatibel with QIHAN free DDNS
- Up to 5 Megapixels resolution recording, storage and playback
- Simultaneous HDMI and VGA output, the resolution is up to 1080P
- Up to 16 channels synchronously playback
- Support instant playback
- Support corridor mode

Model	QH-N6516F-H
<b>Video/Audio Input</b>	
IP Video Input	16 CH
Two-way Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
<b>Network</b>	
Incoming bandwidth	128Mbps
<b>Video/Audio Output</b>	
HDMI Output	1
VGA Output	1
Audio Output	1 CH, RCA
<b>Decoding</b>	
Live View/Playback Resolution	4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Recording Resolution	4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Synchronous Playback	16 CH
<b>Hard Disk</b>	
SATA	8
Capacity	Up to 4TB for each disk
<b>External Interface</b>	
Network Interface	2RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-232, 1 RS-485
USB Interface	2 USB2.0 + 1 USB3.0
Alarm In	8
Alarm Out	2



POE	
Interface	NA
Supported Standard	NA
General	
Power Supply	220V, AC
Consumption	20W (Without Disk) 90W (Fully Configured)
Working Temperature	-10°C~55°C (14°F ~ 131°F)
Working Humidity	10%—90%
Dimensions	86.1mm × 442.0mm ×421.0mm (3.39" × 17.40" × 16.75"), 2U
Weight(without HDD)	5.5KG